

## Tapered roller bearing 33026-JR-JTEKT - 33026-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/33026-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
130	200	55	55	43	390	705	1 700	2 300	33026JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2EE	42.5	142	143	190	178	192	8	12	2	2	0.34	1.76	0.97	6.19

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126086
Inside diameter	130 mm
Inside diameter	5.118" inch
Outside diameter	200 mm
Outside diameter	7.874" inch
Thickness	55 mm
Thickness	2.165" inch
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE