

Tapered roller bearing 32326-JTEKT - 32326-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32326-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
130	280	98.75	93	78	852	1160	1400	1800	32326					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	69.1	152	163	262	226	259	10	15	4	3	0.35	1.73	0.95	26.5

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250277917
Inside diameter	130 mm
Inside diameter	5.118" inch
Outside diameter	280 mm
Outside diameter	11.024" inch
Thickness	98.75 mm
Thickness	3.888" inch
Weight	26500 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE