

Tapered roller bearing 31328-JR-JTEKT - 31328-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/31328-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
140	300	77	70	47	674	865	1 100	1 500	31328JR					
Dimension series to ISO995 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
7GB	93.8	162	167	282	254	280	8	26	4	3	0.83	0.73	0.40	23.3

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419831
Inside diameter	140 mm
Outside diameter	300 mm
Thickness	77 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE