

Tapered roller bearing 33030-JR-JTEKT - 33030-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/33030-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
150	225	59	59	46	3	2.5	459	869	1 500	2 000	33030JR			
Dimension series to ISO955 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁
2EE	47.8	164	164	213	200	217	8	13	2.5	2	0.36	1.65	0.90	8.09

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126130
Inside diameter	150 mm
Outside diameter	225 mm
Thickness	59 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE