

Tapered roller bearing 30332-JR-JTEKT - 30332-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30332-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.							
160	340	75	68	58	938	1220	1100	1400	30332JR						
Dimension series to ISO355 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer.1) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{2a} min.	r _{2a} max.		Y ₁	Y ₀	
268	63.3	162	205	322	289	310	12	17	4	3	0.35	1.74	0.96	31.8	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421278
Inside diameter	160 mm
Outside diameter	340 mm
Thickness	75 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE