

Tapered roller bearing 32034-JR-JTEKT - 32034-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32034-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
170	260	57	57	43	526	905	1 300	1 700	32034JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4EC	55.8	184	187	248	230	249	10	14	2.5	2	0.44	1.35	0.74	10.5

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250123726
Inside diameter	170 mm
Outside diameter	260 mm
Thickness	57 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE