

Tapered roller bearing 30234-JR-JTEKT - 30234-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30234-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
170	310	57	52	43	620	867	1 100	1 500			30234JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4GB	61.2	192	202	292	269	288	8	14	4	3	0.44	1.38	0.76	17.8

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421315
Inside diameter	170 mm
Outside diameter	310 mm
Thickness	57 mm
Weight	17800 g
Packaging	1
Standard	No standard

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE