

Tapered roller bearing 32940-JR-JTEKT - 32940-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32940-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
200	280	51	51	39	3	2.5	486	958	1 100	1 500	32940JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
3EC	53.6	214	216	268	257	271	9	12	2.5	2	0.39	1.52	0.84	9.44

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125775
Inside diameter	200 mm
Outside diameter	280 mm
Thickness	51 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE