

## Tapered roller bearing 30340-D-JTEKT - 30340-D-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/30340-d-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
200	420	89	80	56	904	1230	690	970			30340D

  

Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	122.6	228	248	398	365	385	11	33	5	4	0.81	0.74	0.41	50.6

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421612
Inside diameter	200 mm
Outside diameter	420 mm
Thickness	89 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE