

Tapered roller bearing 32048-JR-JTEKT - 32048-JR-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32048-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
240	360	76	76	57	924	1720	870	1200			32048JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
4FD	78.5	258	261	346	318	346	12	19	3	2.5	0.46	1.31	0.72	26.8	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250123795
Inside diameter	240 mm
Outside diameter	360 mm
Thickness	76 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE