


# Tapered roller bearing

## M12648-M12610-JTEKT - M12648-M12610-JTEKT

https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/m12648-m12610-jtekt

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
22.225	50.005	17.526	18.288	13.970	1.2	1.2	39.1	40.7	8 500	11 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
M12648	M12610	11.1	28.5	26.5	44.0	46.0	1.2	1.2	0.28	2.16	1.19	0.115	0.058

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425450
Inside diameter	22.225 mm
Outside diameter	50.005 mm
Thickness	17.526 mm
Weight	166 g
Packaging	1
Standard	No standard

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE