

Tapered roller bearing 26883R-26822-JTEKT - 26883R-26822-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/26883r-26822-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
35.000	79.375	23.812	25.400	19.050	0.8	0.8	81.1	105	5 000	6 700

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
26883R	26822	16.4	42.5	42.0	71.0	74.0	0.8	0.8	0.32	1.88	1.04	0.414	0.186

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426426
Inside diameter	35 mm
Inside diameter	1.378" inch
Outside diameter	79.375 mm
Outside diameter	3 1/8" inch
Thickness	23.812 mm
Thickness	15/16" inch
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE