

## Tapered roller bearing 4375-4335-JTEKT - 4375-4335-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/4375-4335-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_1$ max.	$r_1$ min.	$C_r$	$C_{10}$	Grease lub.	Oil lub.	
38.100	90.488	39.688	40.386	33.336	1.6	3.2	132	189	4 500	6 000	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
4375	4335	25.6	51.0	48.5	77.0	85.0	1.6	3.2	0.28	2.11	1.16	0.841	0.459

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426679
Inside diameter	38.1 mm
Outside diameter	90.488 mm
Thickness	39.688 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE