

Tapered roller bearing 18587-18520-JTEKT - 18587-18520-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/18587-18520-jtekt>

Single-row tapered roller bearings Koyo
inch series



| Boundary dimensions (mm) | | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|----------------|----------------|----------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | r ₁ | r ₂ | r ₃ | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 39.688 | 73.025 | 16.667 | 17.462 | 12.700 | 0.8 | 1.6 | | 45.9 | 55.8 | 5 200 | 6 900 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|----------|--------------------|----------------|------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 18587 | 18520 | 14.5 | 46.0 | 46.0 | 66.0 | 69.0 | 0.8 | 1.6 | 0.35 | 1.71 | 0.94 | 0.215 | 0.085 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952426693 |
| Inside diameter | 39.688 mm |
| Outside diameter | 73.025 mm |
| Thickness | 16.667 mm |
| Packaging | 1 |

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE