

Tapered roller bearing 3382-3328-JTEKT - 3382-3328-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/3382-3328-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₂ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.	
39.688	84.138	29.370	30.391	22.812	3.6	3.2	91.0	106	5 000	6 700	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> ₃ max.	<i>r</i> ₄ max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
3382	3328	18.7	52.0	45.5	72.0	76.0	3.6	3.2	0.27	2.20	1.21	0.438	0.312

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426723
Inside diameter	39.688 mm
Outside diameter	84.138 mm
Thickness	29.37 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE