


## Tapered roller bearing 28158-28300-JTEKT - 28158-28300-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/28158-28300-jtekt>

Single-row tapered roller bearings Koyo  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
40.000	76.200	20.638	20.940	19.607	1.6	1.2	57.3	65.9	5 300	7 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
28158	28300	16.5	47.5	45.0	68.0	71.0	1.6	1.2	0.40	1.49	0.82	0.266	0.137

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250107252
Inside diameter	40 mm
Outside diameter	76.2 mm
Thickness	20.638 mm
Weight	412 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE