

Tapered roller bearing LM603049-LM603014-JTEKT - LM603049-LM603014-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/lm603049-lm603014-jtekt>

Single-row tapered roller bearings — Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
45.242	79.974	19.842	19.842	19.080	3.6	0.8	57.1	73.5	4 900	6 500

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring		<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.		<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
LM603049	LM603014	17.5	57.0	50.0	71.0	74.0	3.6	0.8	0.43	1.41	0.77	0.243	0.152

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427287
Inside diameter	45.242 mm
Outside diameter	79.974 mm
Thickness	19.84 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE