

# Tapered roller bearing

## LM503349R-LM503310-JTEKT - LM503349R-LM503310-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/lm503349r-lm503310-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
45.987	74.976	18.000	18.000	14.000	2.4	1.6	52.6	74.6	5 000	6 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
LM503349R	LM503310	16.0	53.0	51.0	67.0	72.0	2.4	1.6	0.40	1.49	0.82	0.207	0.095

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427300
Inside diameter	45.987 mm
Outside diameter	74.976 mm
Thickness	18 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE