

## Tapered roller bearing 623-612-JTEKT - 623-612-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/623-612-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
57.150	120.650	41.275	41.275	31.750	3.6	3.2	174	217	3 500	4 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
623	612	27.3	72.0	66.0	105.0	110.0	3.6	3.2	0.31	1.91	1.05	1.27	0.853

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250164552
Inside diameter	57.15 mm
Outside diameter	120.65 mm
Thickness	41.65 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE