

Tapered roller bearing

JLM508748-JLM508710-JTEKT - JLM508748-JLM508710-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/jlm508748-jlm508710-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
60.000	95.000	24.000	24.000	19.000	5.0	2.5	86.1	125	3 900	5 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
JLM508748	JLM508710	21.2	75.0	66.0	85.0	91.0	5.0	2.5	0.40	1.49	0.82	0.402	0.196

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428253
Inside diameter	60 mm
Outside diameter	95 mm
Thickness	24 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE