


Tapered roller bearing 65237A-65500-JTEKT - 65237A-65500-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/65237a-65500-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.	
60.325	127.000	44.450	44.450	34.925	1.6	3.2	208	269	3 300	4 400	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
65237A	65500	35.2	78.0	71.0	107.0	119.0	1.6	3.2	0.49	1.23	0.68	1.59	1.02

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428413
Inside diameter	60.325 mm
Outside diameter	127 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE