

Tapered roller bearing 6382-6320-JTEKT - 6382-6320-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/6382-6320-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub. Oil lub.		
63.500	135.755	53.975	56.007	44.450	4.3	3.2	286	357	3 000	4 000	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
6382	6320	34.8	84.0	77.0	117.0	126.0	4.3	3.2	0.32	1.85	1.02	2.29	1.39

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428512
Inside diameter	63.5 mm
Outside diameter	135.755 mm
Thickness	53.975 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE