

Tapered roller bearing H414235-H414210-JTEKT - H414235-H414210-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/h414235-h414210-jtekt>

Single-row tapered roller bearings inch series Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|----------------------|----------------------|-------------------------|-----------------------|----------------------|--------------------------------------|--|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r_a</i> | <i>r_b</i> | <i>C_r</i> | <i>C₁₀</i> | Grease lub. Oil lub. | | |
| 63.500 | 136.525 | 41.275 | 41.275 | 31.760 | 3.6 | 3.2 | 241 | 308 | 2 900 | 3 800 | |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) | |
|-------------|------------|------------------|--------------------------|----------------------|----------------------|----------------------|---------------------------|---------------------------|----------|----------------------|----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d_a</i> | <i>d_b</i> | <i>D_a</i> | <i>D_b</i> | <i>r_a</i> max. | <i>r_b</i> max. | <i>e</i> | <i>Y₁</i> | <i>Y₂</i> | Inner ring | Outer ring |
| H414235 | H414210 | 30.3 | 82.0 | 78.0 | 121.0 | 129.0 | 3.6 | 3.2 | 0.36 | 1.67 | 0.92 | 2.11 | 0.796 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952428529 |
| Inside diameter | 63.5 mm |
| Outside diameter | 136.525 mm |
| Thickness | 41.275 mm |
| Packaging | 1 |

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE