


Tapered roller bearing

JH211749A-JH211710-JTEKT - JH211749A-JH211710-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/jh211749a-jh211710-jtekt>

Single-row tapered roller bearings — Koyo
Inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.	
65.000	120.000	39.000	38.500	32.000	7.1	2.8	189	255	3 200	4 300	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
JH211749A	JH211710	27.9	88.0	74.0	107.0	114.0	7.1	2.8	0.34	1.78	0.98	1.27	0.618

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428567
Inside diameter	65 mm
Outside diameter	120 mm
Thickness	39 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE