

Tapered roller bearing 759-752-JTEKT - 759-752-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/759-752-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
88.900	161.925	47.625	48.260	38.100	3.6	3.2	273	391	2 400	3 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
759	752	35.5	106.0	99.0	144.0	150.0	3.6	3.2	0.34	1.76	0.97	2.50	1.59

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250203534
Inside diameter	88.9 mm
Outside diameter	161.925 mm
Thickness	47.625 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE