

## Needle roller bearing 9BTM1312-JTEKT - 9BTM1312-JTEKT

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/9btm1312-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) |     |     |          | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                       |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|---|
| $F_w$                    | $D$ | $C$ | $b$ min. | $C_0$                   | $C_{0r}$ | Oil lub.                             | Caged type<br>With open ends    With closed end |
| 9                        | 13  | 12  | 10.4     | 420                     | 5.50     | 35 000                               | <b>9BTM1312</b>                                 |

| Full complement type |                 | Recommended dimensions (mm) |       |                             |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|-------|-----------------------------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (φ6) min.        | max.  | Housing bore dia. (N7) min. | max.   | With open ends    | With closed end |
| —                    | —               | 8.991                       | 9.000 | 12.977                      | 12.995 | 4.6               | 5.2             |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952469430 |
| Inside diameter  | 9 mm          |
| Outside diameter | 13 mm         |
| Thickness        | 12 mm         |
| Weight           | 4.6 g         |
| Packaging        | 1             |

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE