


## Roller bearing NN3092K-JTEKT - NN3092K-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/roller/nn3092k-jtekt>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C</i>	<i>C<sub>02</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
460	680	163	6	—	827	2700	5480	570	690	—	NN3092K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d<sub>a</sub></i>		<i>D<sub>a</sub></i>		<i>r<sub>a</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
—	—	484	—	—	656	632	5	201	195

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952474212
Inside diameter	460 mm
Outside diameter	680 mm
Thickness	163 mm
Weight	195000 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE