


## Roller bearing NA4904UU-JTEKT - NA4904UU-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/roller/na4904uu-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
25	20	37	17	16.4	18.2	8 000	—	

	Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.
	With inner ring	$d_a$ max.	$D_a$ max.	Without inner ring	With inner ring	
NA4904UU	22	35	0.3	—	0.078	IRM202518

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482392
Inside diameter	20 mm
Outside diameter	37 mm
Thickness	17 mm
Weight	78 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE