


## Roller bearing NQ40-20-JTEKT - NQ40-20-JTEKT

<https://www.123bearing.ie/bearing-housing/roller-bearing/roller/nq40-20-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	$C_{10}$	Oil lub.	Without inner ring	
40	35	50	20	—	0.3	27.2	48.8	12 000	NQ40/20
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	$d_1$	$D_1$	$r_1$	0.085	0.129				
	min.	max.	max.						
	37	48	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483030
Inside diameter	40 mm
Outside diameter	50 mm
Thickness	20 mm
Weight	85 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE