

Deep groove ball bearing single row 22338-RHA-JTEKT - 22338-RHA-JTEKT

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/single-row/22338-rha-jtekt>

Boundary dimensions

Asymmetrical rollers: RJR, RJR/G1, RJA
Symmetrical rollers: RJA
Taper bore: Kørc30

22300R / 22000R(RH) / 22200R(RH) / 22300R(RH) / 22400R(RH) / 22500R(RH) / 22600R(RH) / 22700R(RH) / 22800R(RH) / 22900R(RH) / 23000R(RH) / 23100R(RH) / 23200R(RH) / 23300R(RH) / 23400R(RH) / 23500R(RH) / 23600R(RH) / 23700R(RH) / 23800R(RH) / 23900R(RH) / 24000R(RH) / 24100R(RH) / 24200R(RH) / 24300R(RH) / 24400R(RH) / 24500R(RH) / 24600R(RH) / 24700R(RH) / 24800R(RH) / 24900R(RH) / 25000R(RH) / 25100R(RH) / 25200R(RH) / 25300R(RH) / 25400R(RH) / 25500R(RH) / 25600R(RH) / 25700R(RH) / 25800R(RH) / 25900R(RH) / 26000R(RH) / 26100R(RH) / 26200R(RH) / 26300R(RH) / 26400R(RH) / 26500R(RH) / 26600R(RH) / 26700R(RH) / 26800R(RH) / 26900R(RH) / 27000R(RH) / 27100R(RH) / 27200R(RH) / 27300R(RH) / 27400R(RH) / 27500R(RH) / 27600R(RH) / 27700R(RH) / 27800R(RH) / 27900R(RH) / 28000R(RH) / 28100R(RH) / 28200R(RH) / 28300R(RH) / 28400R(RH) / 28500R(RH) / 28600R(RH) / 28700R(RH) / 28800R(RH) / 28900R(RH) / 29000R(RH) / 29100R(RH) / 29200R(RH) / 29300R(RH) / 29400R(RH) / 29500R(RH) / 29600R(RH) / 29700R(RH) / 29800R(RH) / 29900R(RH) / 30000R(RH)

Spherical roller bearings

Bearing No.	Boundary dimensions(mm)			n(min)	Basic load ratings(kN)		Fatigue load limit(kN)		Limiting speeds(min-1)
	d	D	B		Cr	CDr	Cu	Grease lub.	
22338RHA	190	400	132	5	2430	2810	192	870	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060670274
Inside diameter	190 mm
Outside diameter	400 mm
Thickness	132 mm
Limiting speed	870 rpm
Dynamic load	2430 kN
Static load	2810 kN
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE