

## Deep groove ball bearing single row 24084-RHA-JTEKT - 24084-RHA-JTEKT

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/single-row/24084-rha-jtekt>

Boundary dimensions

Asymmetrical rollers: RBR  
Symmetrical rollers: RKR, RHR, RHA  
Taper bore: KorK30

23800R / 23000R(RH) / 23200R(RH) / 23300R(RH) / 23400R(RH) / 23500R(RH) / 23600R(RH) / 23700R(RH) / 23800R(RH) / 23900R(RH) / 24000R(RH) / 24100R(RH) / 24200R(RH) / 24300R(RH) / 24400R(RH) / 24500R(RH) / 24600R(RH) / 24700R(RH) / 24800R(RH) / 24900R(RH) / 25000R(RH) / 25100R(RH) / 25200R(RH) / 25300R(RH) / 25400R(RH) / 25500R(RH) / 25600R(RH) / 25700R(RH) / 25800R(RH) / 25900R(RH) / 26000R(RH) / 26100R(RH) / 26200R(RH) / 26300R(RH) / 26400R(RH) / 26500R(RH) / 26600R(RH) / 26700R(RH) / 26800R(RH) / 26900R(RH) / 27000R(RH) / 27100R(RH) / 27200R(RH) / 27300R(RH) / 27400R(RH) / 27500R(RH) / 27600R(RH) / 27700R(RH) / 27800R(RH) / 27900R(RH) / 28000R(RH) / 28100R(RH) / 28200R(RH) / 28300R(RH) / 28400R(RH) / 28500R(RH) / 28600R(RH) / 28700R(RH) / 28800R(RH) / 28900R(RH) / 29000R(RH) / 29100R(RH) / 29200R(RH) / 29300R(RH) / 29400R(RH) / 29500R(RH) / 29600R(RH) / 29700R(RH) / 29800R(RH) / 29900R(RH) / 30000R(RH)

Spherical roller bearings

Bearing No.	Boundary dimensions(mm)			Basic load ratings(kN)	Fatigue load limit(kN)		Limiting speeds(min-1)
	d	D	B		C <sub>r</sub>	C <sub>0r</sub>	
24084RHA	420	620	200	5	4730	8490	555

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060672148
Inside diameter	420 mm
Outside diameter	620 mm
Thickness	200 mm
Limiting speed	400 rpm
Dynamic load	4730 kN
Static load	8490 kN
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE