

## Tapered roller bearing T5ED065-JTEKT - JH211749-E-10-E-KOYO

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/jh211749-e-10-e-koyo>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
65	120	39	38	31	151	232	3 200	4 300	T5ED065					
Dimension series to ISO355 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
5ED	34.1	83	75	108	96	115	5	8	3	2	0.56	1.07	0.59	1.93

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952408972
Inside diameter	65 mm
Outside diameter	120 mm
Thickness	39 mm
Weight	1908 g
Packaging	1
Standard	No standard

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE