


## Drawn cup roller bearing BAM1014-IKO - BAM1014-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/drawn-cup/bam1014-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
15.875 ( $\frac{5}{8}$ )	—	—	—	—	—	—	—	<b>BAM 1014</b>	16.2	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. h8		Housing bore dia. J7		$C$	$C_0$	rpm	IRB 714
15.875 $\frac{5}{8}$	20.638 $\frac{3}{4}$	22.221 $\frac{7}{8}$	1.3	15.875 Max.	15.864 Min.	20.650 Max.	20.629 Min.	10 700 N	17 500 N	25 000

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952172910
Inside diameter	15.88 mm
Outside diameter	20.64 mm
Thickness	22.22 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE