

## Drawn cup roller bearing BAM108-IKO - BAM108-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/drawn-cup/bam108-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																																					
	Standard	Mass (Ref.) g	Closed end																																															
15.875 ( $\frac{5}{8}$ )	---	---	---	---	---	---	---	---	---	---	---	---	---																																					
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions mm(inch)</th> <th colspan="4">Standard mounting dimensions mm</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="1">Allowable rotational speed(*)</th> <th colspan="1">Assembled inner ring</th> </tr> <tr> <th><math>F_w</math></th> <th><math>D</math></th> <th><math>C</math></th> <th colspan="2">Shaft dia. h8</th> <th colspan="2">Housing bore dia. J7</th> <th><math>N</math></th> <th><math>C_0</math></th> <th><math>N</math></th> <th><math>C_0</math></th> <th>rpm</th> <th>IRB 68-1</th> </tr> </thead> <tbody> <tr> <td>15.875 (<math>\frac{5}{8}</math>)</td> <td>20.638 (<math>\frac{3}{4}</math>)</td> <td>12.70 (500)</td> <td>1.3</td> <td>15.875</td> <td>15.884</td> <td>20.650 / 20.629</td> <td>5 420</td> <td>7 310</td> <td>25 000</td> <td>IRB 68-1</td> </tr> </tbody> </table>														Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed(*)	Assembled inner ring	$F_w$	$D$	$C$	Shaft dia. h8		Housing bore dia. J7		$N$	$C_0$	$N$	$C_0$	rpm	IRB 68-1	15.875 ( $\frac{5}{8}$ )	20.638 ( $\frac{3}{4}$ )	12.70 (500)	1.3	15.875	15.884	20.650 / 20.629	5 420	7 310	25 000	IRB 68-1
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed(*)	Assembled inner ring																																						
$F_w$	$D$	$C$	Shaft dia. h8		Housing bore dia. J7		$N$	$C_0$	$N$	$C_0$	rpm	IRB 68-1																																						
15.875 ( $\frac{5}{8}$ )	20.638 ( $\frac{3}{4}$ )	12.70 (500)	1.3	15.875	15.884	20.650 / 20.629	5 420	7 310	25 000	IRB 68-1																																								

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952172958
Inside diameter	15.88 mm
Outside diameter	20.64 mm
Thickness	12.7 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE