

Drawn cup roller bearing BAM138-IKO - BAM138-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/drawn-cup/bam138-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number																
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g								
20.638 ($\frac{3}{16}$)	—	—	—	—	—	—	—	BAM 138	16.4	—	—						
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	B	Shaft dia. d_6		Housing bore dia. J_7		C	C	C_0	C_0	N	N	rpm			
20.638	26.988	12.70	1.3	20.638	20.625	27.000	26.979	7 170	9 450	19 000	IRB 98						

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173122
Inside diameter	20.64 mm
Outside diameter	26.99 mm
Thickness	12.7 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE