

## Tapered roller bearing 938-932-JTEKT - 938-932-KOYO

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/938-932-koyo>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
114.300	212.725	66.675	66.675	53.975	7.1	3.2	450	674	1 800	2 400

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
938	932	47.6	141.0	128.0	187.0	193.0	7.1	3.2	0.33	1.84	1.01	5.96	4.07

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250209734
Inside diameter	114.3 mm
Outside diameter	212.72 mm
Thickness	53.9 mm
2nd Thickness	66.6 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE