


## Tapered roller bearing 4368-4335-TIMKEN - 4368-4335-TIMKEN

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/4368-4335-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
34.925	90.488	39.688	109000	0.21	51900	25700	2100	29400	4300	
1.3750	3.5625	1.5625	44700		11600	5040		45800	4325	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
40.286	33.338	-15.8	3.5	48.8	55.8	3.3	85.8	77.8	2.2	8.6	52.9	14.3	0.9872	5.36
1.5860	1.3125	-0.59	0.14	1.93	2.17	0.13	3.35	3.03	0.09	0.33			0.281	

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952310275
Inside diameter	34.93 mm
Outside diameter	90.49 mm
Thickness	39.69 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE